

## **Dual Track Spiral**

Two Spirals in a single frame



The Ryson Dual Track Spiral is the ultimate space-saver. Two independent tracks operate within one spiral structure. Both tracks can go up or down, and can optionally be reversible. Their proprietary modular design offers many flexible features and benefits and can help increase productivity and lower your total cost of ownership.

#### **Easy to Install:**

Most Spirals are shipped in one piece, pre-assembled and pre-tested, drastically reducing time and cost of installation.

#### O Modular Design:

Our unique design offers flexibility of configuration. It also adds the ability to field modify to accommodate changing future needs at a fraction of the cost of a new conveyor.

#### **O** Low Maintenance:

Our Spirals and components are designed for reliability. low maintenance and long life. They have an impressive up-time record reducing the total cost of ownership.

#### **O** Built-in Protection:

All Ryson Spirals are equipped with an automatic chain tensioning device and built-in overload protection ensuring safe and reliable operation.



Scan or Click for full details energy, controls and systems integration. **Overlapping Slats:** Overlapping slats provide a smooth and efficient conveying surface, with gentle product handling and suitable for all types of conveyable items.

# **Proprietary**

**Belt Slat:** Our innovative chainslat design enables a low friction operation without any sliding movements or wear-strips. This yields a load carrying capacity of up to 75 lbs per linear foot, and can start and stop fully loaded.

**Efficient:** Our efficient rolling friction

chain-slat design only needs a single drive

per track, resulting in substantial savings in

Finishes: Ryson Spirals are available in powder coated carbon steel. stainless steel wet, hybrid and freezer versions.

**Design Flexibility:** Our Dual Spirals tracks operate independently and can also be designed to feed in, or discharge at different elevations and or directions.




Controls and Integration: Most Spirals are shipped without controls because they typically integrate with an overall conveyor control system. We do offer a number of controls and pre-wiring options. A Variable Frequency Drive (VFD) is required for proper operation of the spirals.



#### **Quick Facts:**

Top Speed:	200 FPM*
Max Height:	45'*
Slat Width:	8" - 20"
Weight Capacity:	50 lbs/lin foot <sup>**</sup>
Total Weight:	Up to 1800 lbs**
VFD Required:	Yes
<b>Optional Controls:</b>	Yes
Custom Options:	Yes
Color Options:	RAL colors
Incline Angle:	Up to 12.5°


\* Some models may have limitations \*\* For Standard Capacity, high capacity is double



#### **Configurations:**

All Ryson Spiral Conveyors are available in several standard versions to accommodate a wide range of loads and applications.

- The individually driven conveyors can be configured to go up or down, clockwise or counter- clockwise and can optionally be reversible.
- All models can be built with extended infeed or outfeed tangents, making our Spiral Conveyors an easy to fit and help simplify the most challenging of layouts.





## **Powder Coated Carbon Steel**

Part	Specifications
Frame	Coated aluminium tube with galvanized load arms
Chain configuration	Nickel plated chain, carbon steel bearings
Finish	Powder Coated in most RAL colors

#### Stainless Steel Hybrid (Dry)

Part	Specifications		
Frame	Coated aluminium center tube zinc plated load arms		
Chain configuration	Nickel plated chain, carbon steel bearings		
Finish	Stainless steel base frame, legs & side guards.		

#### **Stainless Steel (Wet)**

Part	Specifications		
Frame	Stainless steel or coated aluminium tube depending on model. Stainless steel base frame, load arms & fasteners.		
Chain configuration	Nickel plated chain with stainless steel sealed bearings		
Finish	Stainless steel base frame, legs & side guards.		





### VERTICAL CONVEYING SOLUTIONS. WORLDWIDE.

Ryson is a member of the Royal Apollo Group, established in 1847 and headquartered in the Netherlands. Ryson manufactures in USA and supports North America. We have manufacturing in Netherlands, USA, and Thailand with service operations in Netherlands, USA, Thailand, China, India, and Mexico. As one global company, we are the world's leader in Vertical Conveying!

Туре	Diameter	Diameter 1	Diameter	Slat Width	Width
1200-300/2000-300	7'-11" (2400)	6'-6" (2000)	3'-11" (1200)	12" (300)	1'-4" (400)
1300-400/2300-400	9'-3" (2800)	7'-7" (2300)	4'-3" (1300)	16" (400)	1'-8" (500)

Totes

#### **Typically Conveys:**



Cartons











Bundles